

Please fill this order Order confirmation

For office use only


DEALER	Date: _____ Dealer #: _____
	P.O.# _____
	Dealer: _____
Phone: _____ FAX: _____	
CUSTOMER	Customer: _____

	Job Name: _____
Please indicate any special shipment requests for our consideration. Your Order Acknowledgment will provide estimated ship date. Please contact your CSR if the Order Acknowledgment differs from your requirements.	
Requested Ship Date: _____	
<input type="checkbox"/> Ship on or before <input type="checkbox"/> Ship on or after	
Ship to: _____	
<input type="checkbox"/> Truck <input type="checkbox"/> Air <input type="checkbox"/> Prepaid <input type="checkbox"/> Collect <input type="checkbox"/> 3rd Party <input type="checkbox"/> Hold and Call <input type="checkbox"/> Hold for pickup at terminal	
Ship Via: _____	
Special Instructions: _____	
MISCELLANEOUS	<input type="checkbox"/> Custom Presentation Drawings Required – <u>Quantity</u> <input type="checkbox"/> DO NOT manufacture until Custom Presentation Drawings are approved and returned <input type="checkbox"/> Process order without approval of Custom Presentation Drawings
	Ordered by: _____
	Received by: _____

STANDARD EQUIPMENT

Push Button Controls on Platform with Emergency Stop, Key Operation
 All Controls – constant pressure
 Low Voltage Controls - 24 Volt
 Platform Safety Pan
 36" high Platform Guard Panels
 36" x 46" Platform with Non-skid Surface
 15-1/2" long Automatic Folding Access Ramp
 550 lb. Capacity
 Taupe Powder Coat Finish
 U.L. Listed when appropriately equipped
 3/4 HP Motor, 120 V, 60 HZ
 Acme Screw Drive
 Three V-Belt Drive System with Monitoring Device

**Note: This model not available with hydraulic or ball screw drive.*

LIFTING HEIGHT	Measure the EXACT lifting height or "H" dimension. Measurement must be a vertical line taken from the top landing to the bottom landing. Fill in Lifting Height
	Exact Lifting Height (H): _____ in. (mm)
	

MODEL	Check the box by the desired model number.
	<input type="checkbox"/> PL-RA 50 <input type="checkbox"/> PL-RA 72 <input type="checkbox"/> "Stock Unit" Right hand configuration (may be switched in field), with Standard Equipment and No Options.

CONTROLS

Lever-style Call/Send Controls at top and bottom landings with Key Operation

GATES

CI 36" wide (42" high) **Top Landing Gate**

Access **ESI** (Top landing doors by others) - Indicate swing at right

Flush Mount Electric Strike (Top landing doors & gates by others)
 Wood jamb Metal jamb Alum. jamb

Keyed Dead Latch (for use with Flush Mount Electric Strike)

MISCELLANEOUS

Fascia Panel: exact Lifting Height (H) _____ in. (mm)
 36" (914mm) wide


Manual Lowering Device

Optional Color: _____

COMMENTS

Diaarams show "bird's eye view" with lower landino positioned at bottom

TOWER/PLATFORM ORIENTATION



TOP LANDING GATE

